

TECHNICAL SPECIFICATIONS

Telephone IP Network Interface

Gigabit Ethernet IEEE 802.3 10/100/1000 BaseT with RJ45 plug • Compatible with Inmarsat BGAN satellite terminals • Optional IEEE 802.11b/g/n wireless LAN support

Voice Encryption

Secure voice over IP communication on any IP network • strongest and most secure algorithms available today – AES256 and Twofish • 4096 bit Diffie-Hellman key exchange with SHA256 hash function • readout-hash based key authentication • 256 bit effective key length • encryption key is destroyed as soon as the call ends

Device Protection

Encrypted storage system for contacts protects confidential data against unauthorized access • hardened Linux operating system with security-optimized components and communication stacks protects device against outside attacks

GSMK CryptoPhones are the only secure phones on the market with full source code available for independent security assessments. They contain no »proprietary« or »secret« encryption, no backdoors, no key-escrow, no centralized or operator-owned key generation, and require no key registration.

Interoperability

Fully compatible with all GSMK CryptoPhone IP mobile, satellite and fixed-line encryption products • IP PBX integration with virtual extensions

Operational Features

LED call indication • programmable secure phonebook • redial function • ringer and handset volume control • mute function • DND (do not disturb) mode



Trustworthy Voice Encryption

The CryptoPhone IP 19 comes with full source code available for independent review. Finally, you can perform an independent assessment to ensure that you can rely on strong encryption without any backdoors in the communications device that you entrust your security to. The GSMK CryptoPhone IP 19 enables you to put the trust where it belongs – in a trustworthy, open and scientific verification process.

GSMK CryptoPhone technology is based on well-researched algorithms for both encryption and voice processing. It features the strongest encryption available combined with key lengths that provide peace of mind today and in the future.

Dimensions & Weight

230 x 200 x 30 mm / 9.1 x 7.9 x 1.2 in.,
690g / 1.5lbs without footstand (920g / 2.1lbs
with footstand) • black or light gray color scheme

Display

4.3-inch sunlight-readable touch-sensitive TFT LCD
screen with LED backlight @ 480 x 272, 16.7mn
colors

Connectivity

RJ-4P4C headset connector • optional 2x USB
Type A connectors for special communications
equipment

Power

IEEE 802.3ad, Class 1 Power over Ethernet or AC
power 100 to 240 VAC, 50-60 Hz, 7 watts
maximum operating power

EMI/EMC & Safety Approvals

FCC Part 15 Subpart B Class B, CE •
IEC60950-1:2001


Standard Accessories

100-240V AC power adapter • full cable set

Optional Accessories

100-240V AC uninterruptible power supply
• solar panel power pack • headset with
background noise suppression

Encryption Overview



Your Local Distributor:

